

Air & Allied Sales (Pacific) Pty Ltd

23 Precision Street
Salisbury QLD 4107

+617 3272 7999

sales@air-allied.com.au



TTi20 ADJ 3/8" SQ DR TORQUE WRENCH

Product Code: **13831**



TTi20 ADJ 3/8" SQ DR TORQUE WRENCH

3/8" Square Drive Adjustable Industrial Torque Wrench. This TTi20 model is supplied with a 3/8" Reversible Ratchet.

The Norbar range of TTi Wrenches have been designed to guarantee operator comfort, accuracy and ease of usability. They are finished in an attractive and durable satin chrome plate.

Available with a dual scale (Nm and lbf ft) or single denomination torque scale our TTi Wrench range are accurate to +/-3%. TTi torque wrenches are supplied with either a reversible ratchet or a push through ratchet to allow for torque control in both the clockwise and anticlockwise direction. TTi models are available with ratchets, fixed heads or female torque handles.

FEATURES

- * Accuracy: +/-3% of reading exceeds all international standards for torque wrenches.
- * Each wrench is supplied with a traceable calibration certificate.
- * Micrometer Scale for simple and error free setting. (On dual scale wrenches, the micrometer increment applies to the N·m scale.)
- * Quick and Light Adjustment: adjustment over the entire scale can quickly be achieved and with minimal effort in approximately ten complete turns (exact number varies by model).
- * Comfortable, Durable Handle: the handle is constructed using two materials; a base material for strength overlaid with a soft feel grip for comfort and slip resistance.
- * The handle material and lens resist chemicals in common usage in the automotive, aviation and industrial environments.

TECHNICAL SPECIFICATIONS

- * Length: 230 mm
- * Square Size: 3/8"
- * Weight: 0.4 Kg
- * Ratchet Diameter: 30 mm

www.air-allied.com.au

Data contained in this document is copyright of Air & Allied (Pacific) Sales Pty Ltd, and as such cannot be reproduced or redistributed, in part or whole, without the expressed permission of Air & Allied (Pacific) Sales Pty Ltd. Errors and Omissions Excepted.

* Engagements per Revolution: 72

* Accuracy: $\pm 3\%$

* Operates between: 4.00 - 20.00 N·m; 35.00 - 180.00 lbf·in