

## Air & Allied Sales (Pacific) Pty Ltd

23 Precision Street  
Salisbury QLD 4107

+617 3272 7999

[sales@air-allied.com.au](mailto:sales@air-allied.com.au)



## Commercial Air Purifier-Activated Carbon

Product Code: **INOVA-E300-C**



### Commercial Air Purifier-Activated Carbon

Designed for commercial applications, the InovaAir E300C is commonly used in the following chemical environments;

Pharmaceutical  
Scientific laboratories  
Digital graphic production areas  
Mining sites  
Control rooms  
3D Printing  
Advantages

14kg activated carbon filter  
Ducted or freestanding operation  
Lower energy costs with EC Fan  
Highest quality components  
All steel construction  
Fully variable speed control

Filters

Pre-filter

Technostat Bag filter. High efficiency @ 0.3 microns with high dust-holding capacity.

Chemical filtration The Chemical filter contains 14 kilograms of virgin-grade activated carbon. (Other gas filter media types are available upon request.)

Specifications

Dimensions W:40cm x D:40cm x H:87cm (fully assembled)

Weight 42 kgs including filters

[www.air-allied.com.au](http://www.air-allied.com.au)

Data contained in this document is copyright of Air & Allied (Pacific) Sales Pty Ltd, and as such cannot be reproduced or redistributed, in part or whole, without the expressed permission of Air & Allied (Pacific) Sales Pty Ltd. Errors and Omissions Excepted.

Construction Australian Made, Powder Coated Zinc Steel 20 gauge  
Power consumption 16-168 Watts  
Power supply 1-phase 220-240V, 50-60Hz  
Standard Filter  
Configuration 14kg Activated Carbon Filter  
Pre-Filter Technostat Bag filter. High-efficiency sub-micron filtration with viral and bacterial filtration.  
BFE Efficiency > 99.9992% \*\*  
VFE Efficiency > 99.9970% \*\*  
Sound Level 35-62 dB (airflow noise only)  
Operating Temp. Min 0 ° C, Max +45 ° C  
Fan Capacity 100-1300 m3/h  
Fan Type EC Centrifugal Fan (European), designed for continuous 24-hour operation (ball bearing maintenance-free)  
Connection Intake and discharge single 200mm duct.  
Other ducting size options are available.  
Speed Control Integrated fully variable speed control.  
Installation Mobile or stationary.  
Warranty 1-year parts and labour.

Technical and other specifications are subject to change without notice.

\*\*Tested in accordance to Spec MIL-M-36954C By Nelson Labs