Air & Allied Sales (Pacific) Pty Ltd

23 Precision Street Salisbury QLD 4107

+617 3272 7999 sales@air-allied.com.au





1/4" HYDROPNEUMATIC RIVETER

This is an Industrial Hydropneumatic tool for blind rivets and structural high performance Farbolt rivets 3/16" - 1/4" and similar. It also features the ability to hold the rivet in the nose and automatically collect the sheared mandrel in the rear collection chamber.

The tool has a hanger "bar" to allow it to be used with tool suspension systems and is fitted with a swivel exhaust silencer, which greatly reduces operational sound levels. It also features a comfortable, shaped grip enhancing operator comfort.

Standard rivets Ø 4.8mm except for aluminium.

Standard rivets Ø 7.8mm only in aluminium.

The riveting tool is also suitable for X/S Trifar high performance rivets, by assembling the nozzle part no. 71345652.

Attachments RAC171 Operation Manual & Parts List

Specifications

Capacity	Standard Rivets: Ø 4.8 mm, 6 mm, 6.4 mm, 7.8 mm Multistage Rivets &
	Multinox Ø 4.8 mm Tamp: Ø 4.8 mm, 6 mm, 6.4 mm X/S-Trifar: Ø 5.2 mm
Max. Force	17,273 N
Overall Height	340 mm
Overall Length	325 mm
Stroke	25.5 mm
Weight	2.9 kg