### Air & Allied Sales (Pacific) Pty Ltd

23 Precision Street Salisbury QLD 4107

+617 3272 7999

sales@air-allied.com.au



# 25,000kg AIR CHAIN HOIST C/W LOAD LIMITE

**Brand: Toku Product Code: TMH25TC2** 



## 25,000kg AIR CHAIN HOIST C/W LOAD LIMITE

TMH25TC2 25,000kg Cord Controlled, Compact, **Heavy Duty Industrial Air Chain Hoist.** 

#### **COMPLIES WITH AS1418.2**

This NEW TOKU TMH series air chain hoists has the highest lifting speed with the lowest headroom on the hoist market and boasts a Built-In Load Limiter / Overload Protection as standard - an excellent OH&S safety feature and one that cannot be overlooked!

With the M3 classification of mechanism (ISO 4301-1) this high speed air hoist is extremely durable and will guarantee the continuity of your process.

The TMH hoists are designed to operate at full lifting capacity with an air pressure from 4 - 6.3 bar.

For full speed operation the hoist air pressure should be 6.3 bar.

This hoist is for the most demanding applications including Offshore Oil & Gas, Above & Underground Mining, Construction, Tunnelling and many more!

You can specify your desired Height of Lift and Control Length at time of ordering to suit your application perfectly.

#### **Specifications**

Air Cons. (under load)

10,800 l/min (381.3 cfm)

Body Material

Cast Iron

Built-In Load I imiter

Chain Length (std)

3 m \* Contact us if shorter or longer length required

Control Type

Cord Control

Cord Length

(std)

2 m \* Contact us if shorter or longer length required

Hose Size I.D

38.1 mm 25,000 kg (25.0T) Lifting Capacity

Load Limiter

Yes

Min. Hook Distance

1,290 mm

No. of Chain

Speed (download)

3.0 m/min

Speed (upload)

1.4 m/min

Underground Mining Suitable

FEATURES Weight 471 kg

- Built-in Automatic, adjustable load limiter without loss of headroom
- Precise variable speed control
- Optimum control of the load, very precise positioning
- Robust 3 step planetary gearbox
- Failsafe automatic internal disc brake
- Mechanical upper & lower switches
- Cast steel housing
- Internal silencing down to 82 dB(A)
- Alloy safety swivel hooks with safety catch
- High performance rotary vane motor
- Exhaust can be piped away for even further reduced sound levels or to accommodate special exhaust requirements
- Different Chain container options available

#### **Attachments**

TMH25TC2 Spare Parts List\_TKl06
Operation Manual for TOKU TMH Series C&PE\_Air Hoists\_TKl05