Air & Allied Sales (Pacific) Pty Ltd

1/50 Success St Acacia Ridge QLD 4110

+617 3272 7999

sales@air-allied.com.au



6,000kg AIR CHAIN HOIST C/W LOAD LIMITER

Brand: Toku Product Code: TMH6000C2



6,000kg AIR CHAIN HOIST C/W LOAD LIMITER

TMH6000C2 6,000kg Cord Controlled, Compact, Heavy Duty Industrial Air Chain Hoist.

COMPLIES WITH AS1418.2

This NEW TOKU TMH series air chain hoists has the highest lifting speed with the lowest headroom on the hoist market and boasts a **Built-In Load Limiter / Overload Protection as standard** - an excellent OH&S safety feature and one that cannot be overlooked!

With the high M4 classification of mechanism (ISO 4301-1) this high speed air hoist is extremely durable and will guarantee the continuity of your process.

The TMH hoists are designed to operate at full lifting capacity with an air pressure from 4 - 6.3 bar.

For full speed operation the hoist air pressure should be 6.3 bar.

This hoist is for the most demanding applications including Offshore Oil & Gas, Above & Underground Mining, Construction, Tunnelling and many more!

You can specify your desired Height of Lift and Control Length at time of ordering to suit your application perfectly.

Specifications

Air Cons. (under load)

4,300 l/min (151.8 cfm)

Body Material

Cast Iron

Built-In Load Limiter

Yes

Chain Length

(std)

(std)

3 m * Contact us if shorter or

longer length required

Control Type Cord Control

Cord Length

2 m * Contact us if shorter or longer length required

Emergency

Stop

Yes

Hose Size I.D

19 mm

Lifting Capacity

6,000 kg (6.0T)

Load Limiter

Yes

Min. Hook Distance

742 mm

No. of Chain Falls

2

Speed (download)

5.2 m/min

Speed (upload)

2.7 m/min

FEATURES

• Built-in Automatic, adjustable load limiter without loss of headroom

• Precise variable speed control

• Optimum control of the load, very precise positioning

• Robust 3 step planetary gearbox

• Failsafe automatic internal disc brake

• Mechanical upper & lower switches

Cast steel housing

• Internal silencing down to 82 dB(A)

· Alloy safety swivel hooks with safety catch

• High performance rotary vane motor

 Exhaust can be piped away for even further reduced sound levels or to accommodate special exhaust requirements

• Different Chain container options available

Attachments

TMH6000 Dimensions
TMH3000_TMH6000 Chain Buckets & Bags Dimensions
TMH6000C2 Spare Parts List_TKI10
Operation Manual for TOKU TMH Series C&PE_Air Hoists_TKI06

Underground Mining Suitable

Yes

Weight 104 kg