

Air & Allied Sales (Pacific) Pty Ltd

23 Precision Street
Salisbury QLD 4107

+617 3272 7999

sales@air-allied.com.au



1/4" WILDEN DOUBLE DIAPHRAGM PUMP

Brand: **Wilden**

Product Code: **WP-00-9604**



1/4" WILDEN DOUBLE DIAPHRAGM PUMP

Wilden P.025/KZPPP/TNL/TF/KTV Air Operated Double Diaphragm Plastic Pump - Polypropylene - PTFE Diaphragm - 1/4" x 1/4" - P0.25 Original. - Pro-Flo®

Features

Designed for demanding utilitarian type applications that require a robust design

Ensure reliability without sacrificing ease of maintenance

Multitude of elastomer options, including Teflon® (PTFE), to meet your abrasion, temperature and chemical compatibility

Self-priming pumping action

Indefinite dry running ability

Non-metallic construction

Large internal clearances

Compressed air driven

Variable speed

Application Suitable for use in chemical, ceramic, plating and finishing, oil and gas, waste water treatment and paint applications.
Ideal for flooded suction, suction lift, submerged operation and waste applications.

www.air-allied.com.au

Data contained in this document is copyright of Air & Allied (Pacific) Sales Pty Ltd, and as such cannot be reproduced or redistributed, in part or whole, without the expressed permission of Air & Allied (Pacific) Sales Pty Ltd. Errors and Omissions Excepted.

Ideal for flooded suction, suction lift, submerged operation and waste applications.

AODD Pump, PVDF, 1/4" Pro-Flo®, Clamped, Threaded, w/ PTFE

Item: 00-9604

Description: P.025/KZPPP/TNL/TF/KTV

Key Specifications

Discharge Orientation: CENTER SWIVEL

Inlet Orientation: CENTER SWIVEL

Default Max Diameter Solids (in.): 0.02

Discharge Size (in.): 0.25

Max Flow Rate (gpm): 4.8

Inlet Size (in.): 0.25

Max Diameter Solids (in.): 0.02

WILDEN Pump Description: P.025/KZPPP/TNL/TF/KTV

Type: Air Operated Double Diaphragm

Item Number Pump: 00-9604

Port Size: 1/4"

Air Kit: NAK

Wet Kit: NWK

Air Distribution System: Pro-Flo®

Pump Construction: PvdF

Diaphragms: PTFE, Neoprene Back-Up, O-ring, IPD

Valve/ Balls: Teflon

Valve Seats: PvdF with PTFE Encapsulated Viton

Outer Piston:None

Air Chamber: Polypropylene

Center Block: Polypropylene

Air Valve: Polypropylene

Capacity GPM: 4

Capacity Liters/min: 18

Pump Weight Lbs: 4,1

Pump Weight Kilo: 1